



The Perfect Choice for **All Locating Professionals**

- Utilities
- Surveying
- Water & Sewer
- Gas & Oil
- Construction



NEW! Membrane Switch

NEW! IP Rated

- **More Ergonomic**
- **More Durable**
- **More Water Resistant**

























All the accuracy of the 52Cx, with the single-handed operation of the 92XT

Audio Output Signal increases in frequency with gradient

field intensity

Idle frequency = 10 Hz

Display Output Expanding bar-graph indicates polarity (positive

or negative) and relative signal strength

Battery Indicator 4-segment LCD

SPECIFICATIONS*

Gain Adjustable Gain with range indicated by a

4-segment LCD

Gain Memory Gain defaults to Medium when powering off/on

Volume 3 Levels: Muted, Medium, and High

Input Power Supplied by one 9V Alkaline Battery

Battery Life 24 Hours (intermittent usage)

-13°F to 140°F **Operating Temperature**

(-25°C to 60°C)

Overall Length 32.5 in (83 cm)

Nominal Sensor Spacing 20 in (50 cm)

Weight Approximately 2.6 Lbs (1.2 Kg)

Construction High impact ABS

Dust & Water Protection Rated IP54 (when operated with

headphone jack plug installed into jack)



The MAGGIE comes standard with:

- **Padded Carrying Case**
- 9V Alkaline Battery
- Instruction Manual

Order/Info Hotline:

800-999-8280

Order/Info Online:

www.schonstedt.com











an employee-owned company

^{*}Specifications subject to change without notice