

# Leica Viva GS10

## Data sheet



### Engaging software

The Leica Viva GNSS GS10 receiver is accompanied with the revolutionary Captivate software, turning complex data into the most realistic and workable 3D models. With easy-to-use apps and familiar touch technology, all forms of measured and design data can be viewed in all dimensions. Leica Captivate spans industries and applications with little more than a simple swipe, regardless of whether you work with GNSS, total stations or both.



### Infinitely bridging the field to the office

Leica Infinity imports and combines data from your GNSS, total station and level instruments for one final and accurate result. Processing has never been made easier when all your instruments work in tandem to produce precise and actionable information.

### ACC»

### Customer care only a click away

Through Active Customer Care (ACC), a global network of experienced professionals is only a click away to expertly guide you through any problem. Eliminate delays with superior technical service, finish jobs faster with excellent consultancy support, and avoid costly site revisits with online service to send and receive data directly from the field. Control your costs with a tailored Customer Care Package, giving you peace of mind you're covered anywhere, anytime.

# Leica Viva GS10

## GNSS TECHNOLOGY

Self-learning GNSS	Leica RTKplus SmartLink (worldwide correction service)  SmartLink fill (worldwide correction service)	Adaptive on-the-fly satellite selection Remote precise point positioning (3 cm 2D) <sup>1</sup> Initial convergence to full accuracy 20 - 40 min, Re-convergence < 1 min Bridging of RTK outages up to 10 min (3 cm 2D) <sup>1</sup>
Leica SmartCheck	Continuous check of RTK solution	Reliability 99.99%
Signal tracking		GPS (L1, L2, L2C, L5), Glonass (L1, L2, L3 <sup>2</sup> ), BeiDou (B1, B2, B3 <sup>2</sup> ), Galileo (E1, E5a, E5b, Alt-BOC, E6 <sup>2</sup> ), QZSS (L1, L2, L5, LEX <sup>2</sup> ), NavIC L5 <sup>3</sup> , SBAS (WAAS, EGNOS, MSAS, GAGAN), L-band
Number of channels		555 (more signals, fast acquisition, high sensitivity)
GNSS antenna	Standard or Choke-ring	Leica AS10 / AS05 or Leica AR10 / AR20 / AR25

## MEASUREMENT PERFORMANCE & ACCURACY<sup>1</sup>

Time for initialisation		Typically 4 s
Real-time kinematic (Compliant to ISO17123-8 standard)	Single baseline Network RTK	Hz 8 mm + 1 ppm / V 15 mm + 1 ppm Hz 8 mm + 0.5 ppm / V 15 mm + 0.5 ppm
Post processing	Static (phase) with long observations Static and rapid static (phase)	Hz 3 mm + 0.1 ppm / V 3.5 mm + 0.4 ppm Hz 3 mm + 0.5 ppm / V 5 mm + 0.5 ppm
Code differential	DGPS / RTCM	Typically 25 cm

## COMMUNICATIONS

Communication ports	Lemo Bluetooth®	1 x USB and 2 x RS232 serial and Power Bluetooth® v2.00 + EDR, class 2
Communication protocols	RTK data protocols NMEA output Network RTK	Leica, Leica 4G, CMR, CMR+, RTCM 2.2, 2.3, 3.0, 3.1, 3.2 MSM NMEA 0183 V 4.00 and Leica proprietary VRS, FKP, iMAX, MAC (RTCM SC 104)
External data links	Up to 3 simultaneously	GSM / GPRS / UMTS / CDMA / VHF / UHF (up to 28800 bps over air) modem Phone / Radio modem in Leica GFU housing (IP67)

## GENERAL

Field controller and software	Leica Captivate software Leica SmartWorx Viva software	Leica CS20 field controller, Leica CS35 tablet Leica CS10 and CS15 field controller
User interface	Buttons and LEDs Web server	On / Off and Function button, 8 status LEDs Full status information and configuration options
Data recording	Storage Data type and recording rate	Removable SD card, 8 GB Leica GNSS raw data and RINEX data up to 20 Hz
Power management	Internal power supply External power supply Operation time <sup>4</sup>	2 exchangeable Li-Ion batteries (6 Ah / 7.4 V) Nominal 12 V DC, range 10.5 - 28 V DC 15h receiving (Rx) data with UHF radio, 13 h transmitting data with UHF radio (1W), 14 h Rx / Tx data with phone modem
Weight and Dimensions	Weight Dimensions	1.20 kg (GS10) / 5.40 kg standard RTK rover setup using pole and backpack 212 mm x 166 mm x 79 mm
Environmental	Temperature Drop Proof against water, sand and dust  Vibration  Humidity  Functional shock	-40 to 65°C operating, -40 to 80°C storage Withstands topple over from a 2m survey pole onto hard surfaces IP68 (IEC60529 / MIL STD 810G 506.5 I / MIL STD 810G 510.5 I / MIL STD 810G 512.5 I) Withstands strong vibration (ISO9022-36-08 / MIL STD 810G 514.6 Cat.24)  100% (ISO9022-13-06 / ISO9022-12-04 / MIL STD 810G 507.5 I)  40 g / 15 to 23 msec (MIL STD 810G 516.6 I)

LEICA VIVA GS10 - GNSS RECEIVER	Basic	Performance	Unlimited
<b>SUPPORTED GNSS SYSTEMS</b>			
Multi-frequency	•	✓	✓
GPS / GLONASS / Galileo / BeiDou	✓ / • / • / •	✓ / • / • / •	✓ / ✓ / ✓ / ✓
<b>RTK PERFORMANCE</b>			
DGPS/RTCM. RTK Unlimited, Network RTK	•	✓	✓
SmartLink fill / SmartLink	• / •	• / •	✓ / •
<b>POSITION UPDATE &amp; DATA RECORDING</b>			
5 Hz / 20 Hz positioning	✓ / •	✓ / ✓	✓ / ✓
Raw data / RINEX data logging / NMEA out	✓ / • / •	✓ / • / •	✓ / ✓ / ✓
<b>ADDITIONAL FEATURES</b>			
RTK reference station functionality	•	✓	✓

✓ Standard

• Optional

<sup>1</sup> Measurement precision, accuracy, reliability and time for initialisation are dependent upon various factors including number of satellites, observation time, atmospheric conditions, multipath etc. Figures quoted assume normal to favourable conditions. A full BeiDou and Galileo constellation will further increase measurement performance and accuracy.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc. Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2015. 774162en - 11.17

<sup>2</sup> Believe to comply, but subject to availability of BeiDou ICD and Galileo commercial service definition. Glonass L3, BeiDou B3, QZSS LEX and Galileo E6 will be provided through future firmware upgrade.

<sup>3</sup> Support of NavIC L5 is incorporated and will be provided through future firmware upgrade.

<sup>4</sup> Might vary with temperature, age of battery, transmit power of data link device.