

# Leica iCON CC200 Field controller Datasheet



## LEICA iCON CC200 – Your new on-site partner!

- Large 10" screen size
- Increased performance, ideal for handling large amounts of data
- Hard keys with user-customisable shortcuts
- 'Glove' and 'rain' modes for all weather conditions
- Up to 12 hours operating time
- Anti-reflective (AR) screen
- 'Portrait' mode to support specific applications

The rugged 10" Leica iCON CC200 field controller is your on-site partner that promises to deliver longer operating times and more comfort, thanks to its single 12-hour battery and large screen. The iCON CC200 is designed to smoothly handle use cases requiring large amounts of data. Used in combination with Leica iCON site or Leica iCON build construction field software, it is the ideal solution for all positioning and measuring tasks on your construction site – including on-machine applications.

[leica-geosystems.com](http://leica-geosystems.com)



- when it has to be **right**

**Leica**  
Geosystems

# Leica iCON CC200 Field controller



<b>MODEL</b>		<b>CC200</b>
Operating system	Microsoft Windows® 10 enterprise LTSC	
CPU platform	Intel® Core™ i5-10310U vPro™ processor 1.7 GHz with Turbo Boost up to 4.4 GHz, 6 MB cache	
RAM	16 GB	
Data storage	512 GB OPAL SSD	
Display	10" widescreen, 1920 × 1200 resolution, anti-reflective (AR) screen, Intel UHD Graphics, concealed mode; day/night mode, Gorilla Glass 3, 10-finger multitouch	
Display branding	Printed display glass	
Keyboard & buttons	IP55 2-button digitiser pen (right click & erase), stylus holder, tether and cleaning cloth Supports 'glove' and 'rain' mode 7 tablet buttons (3 user-definable, A1/A2/A3) On-screen QWERTY keyboard	
I/O ports	1 x USB-C v5.1; 1 x USB A v5.1; Docking station connector (24 pin); Integrated dual-array microphone; Interated 88 db speakers; Intel high definition audio compliant	
<b>COMMUNICATIONS</b>		
Integrated communications	Integrated 4G LTE multi-carrier mobile broadband; Intel wi-fi 6 AX201; Bluetooth® v5.1 (Class 1) <sup>1</sup>	
Integrated GPS	L1 GNSS integrated (depending on country variant)	
Integrated camera	1080 p webcam w/privacy cover & dual-array microphone – infrared with Windows Hello support 8 MP rear camera with autofocus and LED flash	
TPS 1-man mode working range <sup>2</sup>	Typically 450 m, up to 500 m with direct line of sight	
<b>POWER MANAGEMENT</b>		
Battery	Li- ion long 'life' battery: 10.8 V, 6300 mAh	
Operating Time <sup>3</sup>	12 hours (max. load test)	
<b>SPECIFICATIONS</b>		
Size	27.94 cm x 18.8 cm x 2.8 cm (11.0" x 7.4" x 1.1")	
Weight	1.3 kg (2.9 lbs)	
Operating temperature	-30 °C (-20 °F) to 60 °C (140 °F)	
Storage temperature	-50 °C (-60 °F) to 70 °C (160 °F)	
Rain and dust	IP65	
Humidity	95% RH temp cycle 32 °C ( 91 °F) / 71 °C ( 160 °F)	
Drop	1.80 m	
Vibration	General minimum integrity and helicopter minimum integrity test, MIL-STD-810H, Method 514.8, Procedure I, II	

1) Availability of 4G LTE modem dependent on country variant.

2) Range varies depending on local conditions.

3) In continuous field operation mode. May vary with temperature, battery age etc.

Leica iCON. Understanding construction.

The Bluetooth® trademarks are owned by Bluetooth SIG, Inc.  
Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland – 2022.  
Leica Geosystems AG is part of Hexagon AB. 973769en – 08.22

**Leica Geosystems AG**  
Heinrich-Wild-Strasse  
9435 Heerbrugg, Switzerland  
+41 71 727 31 31

- when it has to be **right**

**Leica**  
Geosystems